



MODEL	LG120DT	
Power type	Diesel	
Rated capacity(kg)	12000	
J Load center(mm)	600	
H1 STD Max lifting height(mm)	3500	
L5*W*T STD Fork size(mm)	1520x200x85	
Mast tilt angle(deg)	6/12	
L3 Front overhang(mm)	730	
L4 Rear overhang(mm)	720	
L Overall length(with fork)(mm)	5770	
W1 Overall width(mm)	2350	
H2 STD Mast lowered height(mm)	3170	
H4 Overhead guard height (mm)	2610	
R1 Min.turning radius (mm)	4300	
Min.intersecting aisle(mm)	6750	
Max traveling speed(km/h)load/unload	25/27	
Max lifting speed(mm/s)load/unload	350/370	
Max gradient(%)	20	
Self weight(kg)	15400	
S/P Tread(front/rear)(mm)	1724/1850	
L2 Axle distance(mm)	2950	
Min ground clearance	M2 Mast(mm)	250
	M1 Frame(mm)	360
STD Engine	Cummins QSB4.5-C160	
Rated power(kw)	119	

Optimal Engine(for12t)					
Engine Model	Manufacturer	Rated Power (kw/rpm)	Max.Torque (Nm/rpm)	Bore/Number of Cylinders/Displacement (mm/L)	Fuel Consumption (g/kW·h)
QSB4.5-C160	Cummins	119/2200	624/1400	107/4/4.5	230
CA8DF3	Xichai	118/2200	640/1300	110/6/7.12	230

MOTORPART
DISTRIBUIDORA

LG120DT

Cabin with Broad View
Excellent Stability and Security
Advanced Ergonomical Design
Powerful Turbocharged engine



LG120DT

- Rated Power (kW): 119
- Rated Capacity (kg): 12000
- Power Type: DIESEL

MOTORPART
DISTRIBUIDORA

Juan Pablo II 265 Bis
Rosario | Santa Fe.
Tel. +54 341 458 7887
www.motorpart.com.ar

Para más información sobre productos Lonking
por favor contacte a nuestro agente local

LONKING 龙工
Efficiency Rules the Future

Las especificaciones y el diseño están sujetos a cambios sin previo aviso.
Las imágenes mostradas pueden no incluir accesorios opcionales.