

# FULL ELECTRIC PALLET TRUCK

## EPT15/20

- Imported driving force, strong power.
- 48V maintenance free brushless motor system.
- An integrated battery side pull mechanism that has obtained national patents.
- Adopting a multifunctional intelligent controller and control system, practical and simple.

- 进口驱动力，动力强劲。
- 48V免维护无刷电机系统。
- 获得过国家专利的一体式电池侧拉机构。
- 采用多功能智能手柄和控制系统，实用又简单。

COLOR  
VERDE



手柄(handle)



侧拉(Pull up and replace)



油缸(Cylinder)

### 产品详细参数表 Product detailed parameter

|                                                                                 |                              |             |     |      |
|---------------------------------------------------------------------------------|------------------------------|-------------|-----|------|
| 型号 Model                                                                        | EPT15/20                     |             |     |      |
| 操作类型 Operation type                                                             | 步行式Walkie style              |             |     |      |
| 最大载荷 Rated capacity                                                             | kg                           | 1500/2000   |     |      |
| 载荷中心距 Load center distance                                                      | mm                           | 600         |     |      |
| 前悬距 Front overhang                                                              | x                            | 946         |     |      |
| 轴距 Wheel base                                                                   | y                            | 1200        |     |      |
| 自重 Weight                                                                       | kg                           | 120         | 130 |      |
| 桥负荷（驱动/承重）标准 Load per axle (driving/bearing)                                    | 满载 Laden                     | kg          | 500 | 1100 |
|                                                                                 | 空载 Unladen                   | kg          | 120 | 130  |
| 轮子材质 Material                                                                   | PU                           |             |     |      |
| 轮子数量 Number of wheels                                                           | 1/4                          |             |     |      |
| 驱动轮尺寸 Drive wheel size                                                          | mm                           | φ160*55     |     |      |
| 承重轮尺寸 Load size                                                                 | mm                           | φ80*70      |     |      |
| 承重轮中心距 Load wheel center distance                                               | b2(mm)                       |             |     |      |
| 提升高度 Lift height                                                                | h3(mm)                       | 115         |     |      |
| 货叉降低时高度 Fork height when lowering                                               | h13(mm)                      | -           |     |      |
| 整车总长 Overall length                                                             | l1(mm)                       | 1590        |     |      |
| 车体长度（不含货叉） Body length(No forks)                                                | l2(mm)                       | 440         |     |      |
| 货叉总宽 Fork outer width                                                           | b1(mm)                       | 560         | 685 |      |
| 货叉尺寸 Fork size                                                                  | s/e/l(mm)                    | 50/160/1150 |     |      |
| 货叉外宽 Fork outer width                                                           | b3(mm)                       | 560         | 685 |      |
| 最小离地间隙 Min.ground clearance                                                     | mm                           | 28          |     |      |
| 直角堆垛通道宽度，托盘800x1200/1200沿货叉放置                                                   | Ast(mm)                      |             |     |      |
| Right angle stacking channel width, pallet 800x1200/1200 Placing along the fork |                              | 2155        |     |      |
| 转弯半径 Turning radius                                                             | mm                           | 1380        |     |      |
| 行驶速度满载/空载 Driving speed laden/unladen                                           | km/h                         | 4.0/5.0     |     |      |
| 提升速度满载/空载 Lncrease speed laden/unladen                                          | mm/s                         | 20/25       |     |      |
| 下降速度满载/空载 Descent speed laden/unladen                                           | mm/s                         | 50/40       |     |      |
| 循环工作时间 Cycling work time                                                        | h                            | ≥4          |     |      |
| 行车制动 Service brake                                                              | 电磁制动 Electromagnetic braking |             |     |      |
| 驱动电机功率 Drive motor power                                                        | kw                           | 0.8         |     |      |
| 油泵电机功率 Pump motor power                                                         | kw                           | 0.5         |     |      |
| 系统电压 System Voltage                                                             | v                            | 48          |     |      |
| 控制类型 Control type                                                               | 电动控制 Electrically controlled |             |     |      |
| 驾驶员耳边噪音水平 Noise level                                                           | dB                           | ≤70         |     |      |

Los datos y características pueden actualizarse o modificarse sin previo aviso