



电动托盘堆垛车 — PSL15

FULL-ELECTRIC STACKER

- High performance, large capacity battery, suitable for long-term operation.
- High quality communication drive wheels ensure high performance and low maintenance costs.
- Adopting a multifunctional intelligent handle control, the 48V maintenance free brushless motor system is practical and simple.

- 高性能、大容量电池，适合长时间操作。
- 高质量交流驱动轮确保高性能并维护成本低。
- 采用多功能智能手柄控制，48V免维护无刷电机系统，实用又简单。



COLOR
VERDE



油缸(Cylinder)



手柄(Handle)



驱动轮(Driving wheel)

产品详细参数表 Product detailed parameter

型号 Model		PSL15-16	PSL15-20	PSL15-25	PSL15-30	PSL15-35
操作类型 Operation type		步行式 Walkie				
提升高度 Lift height	h(mm)	1600	2000	2500	3000	3500
最大载荷 Rated capacity	q(kg)			1500		
载荷中心距 Load center distance	c(mm)			500		
前悬距 Front overhang	x(mm)			715		
轴距 Wheel base	y(mm)			1125		
自重 Weight	kg	480	510	530	550	570
轮子材质 Material		PU				
平衡轮尺寸*数量 Balance wheel size φ NO.	φmm			φ110*50*1		
承重轮尺寸*数量 Load wheel size φ NO.	φmm			φ80*70*4		
驱动轮直径 Driving wheel Dia.	φmm			φ160		
驱动轮中心距 Balance wheel center distance	A1(mm)			523		
承重轮中心距 Load wheel center distance	A2(mm)			505		
门架最低高度 Lowered mast height	H1((mm)	2070	1530	1800	2050	2300
作业时门架最大高度 Max.mast height In work	H2((mm)	2070	2520	3020	3520	4020
货叉最低高度 Lowest height of fork	H3(mm)			≤90		
整车总长 Overall length	L1((mm)			1788		
箱体长度 Body length	L2*L4((mm)			443*820		
货叉尺寸 Fork size	S/E/L5((mm)			62/170/1150		
货叉外宽 Fork outer width	L3((mm)			560/685		
最小离地间隙 Min.ground clearance	H5((mm)			20		
通道宽度带1000*1200托盘 Channel width with 1000 * 1200 pallets	Ast(mm)			2100		
转弯半径 Turning radius	mm			1520		
行驶速度满载/空载 Driving speed laden/unladen	km/h			4.0/4.5		
提升速度满载/空载 Lift speed laden/unladen	m/s			0.075/0.09		
最大爬坡能力满载/空载 Maximum climbing capacity laden/unladen	%			6/15		
驱动电机功率 Drive motor power	kw			AC 48V/1.0KW		
油泵电机功率 Pump motor power	kw			DC 48V/1.6KW		
蓄电池容量 Battery capacity	V/AH			48V40AH		
蓄电池重量 Battery weight	kg			9*4		
蓄电池类型 Battery type				牵引铅酸电池 Traction Battery		
驾驶员耳边噪音水平 Noise level	Db(A)			≤70		
门架类型 Frame type				10H+10C		
链条数量 Number of chains				1		

Los datos y características pueden actualizarse o modificarse sin previo aviso