



电动托盘搬运车 — PT30

FULL ELECTRIC PALLET TRUCK

- Imported driving force, strong power.
- 48V maintenance free brushless motor system.
- Adopting a multifunctional intelligent controller and control system, practical and simple.
- The back adopts a thickened baffle for easy maintenance and can effectively protect the safety of goods.

- 进口驱动力，动力强劲。
- 48V免维护无刷电机系统。
- 采用多功能智能手柄和控制系统，实用又简单。
- 背部采用加厚挡板检修方便，还能有效保护货物安全。

COLOR
VERDE



油缸(Cylinder)



气弹簧 (gas spring)



安全挡板(Safety baffle)



驱动轮(Driving wheel)

产品详细参数表 Product detailed parameter

型号 Model		PT30	
操作类型 Operation type		步行式 Walkie style	
最大载荷 Rated capacity	Qkg	3000	
载荷中心距 Load center distance	mm	500	
前悬距 Front overhang	x	1007	
轴距 Wheel base	y	1357	
自重 Weight	kg	220	225
轮子材质 Material		PU	
驱动轮尺寸 Drive wheel size	mm	φ210*70	
承重轮尺寸 Load size	mm	φ80*80	
承重轮中心距 Load wheel center distance	b2(mm)	390	515
提升高度 Lift height	h3(mm)	105	
货叉降低时高度 Fork height when lowering	h13(mm)	82+/-2	
整车总长 Overall length	l1(mm)	1700	
货叉总宽 Fork outer width	b1(mm)	560	685
货叉尺寸 Fork size	s/e/l(mm)	60/170/1200	
货叉外宽 Fork outer width	b3(mm)	560	685
最小离地间隙 Min.ground clearance	mm	24	
直角堆垛通道宽度，托盘800x12001200沿货叉放置 Right angle stacking channel width, pallet 800x12001200 Placing along the fork	Ast(mm)	1919	1919
转弯半径 Turning radius	mm	1508	1508
行驶速度满载/空载 Driving speed laden/unladen	km/h	4/4.5	
提升速度满载/空载 Lift speed laden/unladen	mm/s	20/25	
下降速度满载/空载 Descent speed laden/unladen	mm/s	56/46	
循环工作时间 Cycling work time	h	≥4	
行车制动 Service brake		电磁制动Electromagnetic braking	
驱动电机功率 Drive motor power	kw	AC 48V/1.2KW	
油泵电机功率 Pump motor power	kw	DC 48V/0.8KW	
蓄电池容量 Battery capacity	AH	标配铅酸电池Standard lead-acid battery	40Ah
系统电压 System Voltage	V	48	
控制类型 Control type		电动控制 Electrically controlled	
驾驶员耳边噪音水平 Noise level	dB	≤70	

Los datos y características pueden actualizarse o modificarse sin previo aviso