

SEMI-ELECTRIC PALLET TRUCK
PTL15S

- Low usage and maintenance costs, with a long lifespan.
- Integrated battery pull-up mechanism, quick replacement of battery pack in 5 seconds.
- Obtained a national dual electric drive patent, with strong, stable and reliable power.
- Comfortable rubber handle designed in accordance with ergonomics, ensuring maximum safety and comfort.

- 使用成本及维护成本超低、寿命长。
- 一体式电池上拉机构，5秒快速更换电池组。
- 获得国家双电驱动专利，动力强劲、平稳可靠。
- 符合人体工程学设计的舒适橡胶手柄，确保最大安全性以及舒适度。

COLOR
VERDE

PU轮(PU wheel)



侧拉(Pull up and replace)



电池组 (Accumulator)

产品详细参数表 Product detailed parameter

型号 Model	PTL15S		
操作类型 Operation type		步行式 Walkie style	
最大载荷 Rated capacity	kg	1500	
载荷中心距 Load center distance	mm	500	
轴距 Wheel base	mm	1200	1270
自重 Weight	kg	102	108
轮子数量 Number of wheels		2/4	
驱动轮尺寸 Drive wheel size	mm	φ180*50	
承重轮尺寸 Load size	mm	φ80*68	
轮子材质 Material		PU	
承重轮中心距 Load wheel center distance	b2(mm)	390	525
提升高度 Lift height	h3(mm)	100	
货叉降低时高度 Fork height when lowering	h13(mm)	83	
整车总长 Overall length	l1(mm)	1546	1616
货叉总宽 Fork outer width	b1(mm)	550	685
货叉尺寸 Fork size	s/e/l(mm)	54/160/1150	54/160/1220
货叉外宽 Fork outer width	b3(mm)	550	685
最小离地间隙 Min.ground clearance	mm	23	
直角堆垛通道宽度, 托盘800x1200x1200沿货叉放置 Right angle stacking channel width, pallet 800x1200x1200 Placing along the fork	Ast (mm)	1900	1970
转弯半径 Turning radius	mm	1470	1530
行驶速度满载/空载 Driving speed laden/unladen	km/h	3.5/4.0	
最大爬坡能力满载/空载 Maximum climbing capacity laden/unladen	%	3/6	
驱动电机功率 Drive motor power	kw	0.45*2件 piece	
蓄电池容量 Battery capacity	V/AH	48V/15Ah	
蓄电池类型 Battery type		锂电池 Lithium battery	
控制类型 Control type		电动控制 Electrically controlled	
驾驶员耳边噪音水平 Noise level	dB	≤70	

Los datos y características pueden actualizarse o modificarse sin previo aviso