

FULL-ELECTRIC STACKER TANK15

COLOR
VERDE

- Optional electronic steering system.
- High quality communication drive wheels ensure high performance and reduce maintenance costs.
- In 2016, won the most influential design award in China, the Chinese Design Red Star Award.
- The foldable pedal with rubber lining provides greater flexibility when operating in narrow spaces, and prolonged operation effectively reduces labor intensity.

- 可选配电子转向系统。
- 高质量交流驱动轮确保高性能减少维护成本。
- 2016年获得中国最具影响力设计奖项《中国设计红星奖》。
- 带橡胶衬套的可折叠踏板，在狭小空间操作时灵活性更高，且长时间操作有效降低劳动强度。



护臂(Steering guard arm)



手柄(Handle)



驱动轮(Driving wheel)

产品详细参数表 Product detailed parameter

型号 Model		TANK15-16	TANK15-25	TANK15-30
操作类型 Operation type			站驾式 Stand-on	
最大载荷 Rated capacity	kg		1500	
载荷中心距 Load center distance	mm		400	
前悬距 Front overhang	mm		715	
轴距 Wheel base	mm		1125	
轮子材质 Material			PU	
平衡轮尺寸*数量 Balance wheel size $\varnothing$ NO.	$\varnothing$ mm		$\varnothing 110 \times 50 \times 2$	
承重轮尺寸*数量 Load wheel size $\varnothing$ NO.	$\varnothing$ mm		$\varnothing 80 \times 70 \times 4$	
驱动轮直径 Driving wheel Dia.	$\varnothing$ mm		$\varnothing 210$	
承重轮轮距 Load wheel center distance	mm		523	
提升高度 Lift height	mm		505	
门架最低高度 Lowered mast height	mm	2080	1750	1990
提升高度 Lift height	mm	1600	2500	3000
货叉降低时高度 Fork lowest height	mm		≤ 90	
整车总长 Overall length	mm		1850	
箱体长度 Body length	mm		443*820	
货叉外宽 Fork outer width	mm		685	
货叉尺寸 Fork size	mm		62*170*1150	
最小离地间隙 Min.ground clearance	mm		14	
通道宽度带1000*1200托盘 1000 * 1200 Pallets	mm		2100	
转弯半径 Turning radius	mm		1940	
行驶速度满载/空载 Driving speed laden/unladen	km/h		5/6	
提升速度满载/空载 Lift speed laden/unladen	m/s		0.043/0.056	
最大爬坡能力满载/空载 Maximum climbing capacity laden/unladen	%		6/12	
行车制动 Service brake			电磁制动 Electromagnetic braking	
驱动电机功率 Drive motor power	kw		AC48V/1.	2Kw
油泵电机功率 Pump motor power	kw		DC 48V/1.6Kw	
蓄电池容量 Battery capacity	AH		12V 70Ah*4 / 12V80Ah*4	
蓄电池类型 Battery type			牵引铅酸电池 Traction Battery	
驾驶员耳边噪音水平 Noise level	Db(A)		≤ 70	

Los datos y características pueden actualizarse o modificarse sin previo aviso